

Model - AIS-7600H Series AHD-DVR

Performance Parameters:

Product	Model No	AIS-7604H & AIS-7608H
Sensor	Main Board Sensor	Industrial Embedded Microprocessor
	Operating System	Embedded LINUX operating system
System	Video Coding	H.264
	Coding Resolution	4CH/8CH 720P (1280x720)
	Video Frame	PAL:1~25FP/S ; NTSC : 1~30FP/S
	Video Bit Rate	512Kbps-4096Kbps , Customize , Default to be 2048Kbps
	Stream Type	Video Streaming / Composite Stream
	Double Stream	Support
	Audio Coding	G.711
Video Spec	Video Input	4CH/ 8CH BNC Port
	Video output	1CH CVBS,1CH VGA output,1CH HDMI port
Audio Ports	Audio Input/Output	4CH RCA Audio Input / 1CH RCA Audio Output
	Audio Intercom	Audio Input-Output Multiplexing
Recording Manage	Recording Mode	Automatic recording, Manual Recording, Motion Detection Recording,
	Playback	4CH 720P/8CH Playback (All channel real-time 25FPS)
	Backup Mode	Mobile Hard Disk / U-Hard-Disk / Network
Network	Protocol	Support TCP/IP、UDP、RTP/RTSP、DHCP、PPPoE、DDNS、NTP etc.
	IE Control	With WEB Server to modify configuration parameters and remote control IE
	P2P Cloud	Support login via www.yunyis.com to meet One-Key Remote Control.
	Mobile Remote	Support IOS, Android , Blackberry, Symbian, Software .
HDD	HDD Port	Support 1 pc SATA port max 4TB , No e-SATA port.
Interface	Network/USB	1↑ RJ45 port, 100M E-internet Port ; 2PCS USB Port
	Interface	1PC Standard RJ485 port
Others	Power/Consumption	DC12V ; <15W(No HDD)
	Temperature/Humidity	Temperature:-10°C - + 55°C / Humidity: 10%~90%
	Size/Weight	225mm×215mm×55mm / According package Carton

Model - AIS-7600H Series AHD-DVR



Applications Diagram

